



FirePoint

5000



**RADIO DOME SOUNDER
INSTALLATION MANUAL**

Table of Contents

Section	Page No
1. LOGGING ON A DOME SOUNDER	3
2. SOUNDER VOLUME	5
3. UNIT TAMPER	6
4. DOME SOUNDER INSTALLATION	7

1. Logging on a Dome Sounder

If the installation has been ordered as a complete system, the devices and panel will be supplied already “pre-programmed”. In this scenario go straight to the “Sounder Volume” section. Otherwise, when the dome sounders are purchased separately, they must be added manually to the system. The process of adding radio devices to the 5000 FirePoint Control Panel, is largely carried out automatically, by the panel’s own operating system. It is usual practice for each device to require “logging on” to the system. In such cases, the following action must be taken.

The Dome sounder is shown below, in Figure 1, with the base removed. When removing the AA battery as shown below, the logon button is exposed.




Figure 1

The dome sounder can be programmed to the system by the following procedure:


To log the device onto the 5000 FirePoint, take the device to the front of the panel. Insert the key into the Panels Control Key switch, located on the bottom right of the Panel.

Step No	Action	Screen Display
1	With the key in the “ON” position, the screen will display:	<div style="border: 1px solid black; background-color: #e0ffe0; padding: 5px; text-align: center;"> <p>Panel in Access</p> <p>Date Time</p> </div>
2	Press the “0” key and the screen will now display:	<div style="border: 1px solid black; background-color: #e0ffe0; padding: 5px; text-align: center;"> <p> ***Options *** * </p> <p>> Passwords <</p> <p> Time and Date </p> <p>Yes =Select Time</p> </div>
3	Press the “▽” key until the screen displays:	<div style="border: 1px solid black; background-color: #e0ffe0; padding: 5px; text-align: center;"> <p> Logging </p> <p>> Fire System Opts <</p> <p> Remote Access </p> <p>Yes = select Time</p> </div>
4	Press the “YES” key and the screen will now display:	<div style="border: 1px solid black; background-color: #e0ffe0; padding: 5px; text-align: center;"> <p> ** Fire system ** </p> <p>> Dev. Disable/Test<</p> <p> Net. Disable/Test </p> <p>Yes= Select Time</p> </div>


EMS 5000 FIREPOINT

5	Press the "∇" key until the screen displays:	<pre> System Mode >Engineers Config < Printer Options Yes= Select Time</pre>
6	Press the "YES" key and the screen will now display:	<pre>Enter Your PIN For Access> Then Press YES Time</pre>
7	Press 221100 then press the "YES" key and the screen will display:	<pre> ** Eng.; Config ** > Device Database < Sounder Options Yes= Select Time</pre>
8	Press the "∇" key until the screen displays:	<pre> Sounder Options > Log On Devices < Site Survey Yes= Select Time</pre>
9	Press the "YES" key and the screen will now display:	<pre>Logon DISABLED(000) Push YES to change Push NO to escape Push YES/NO Time</pre>
10	Press the "YES" key to change and the screen will now display:	<pre> **Logon Options** > Logon Slot :AUTO< Slot is :FREE Yes= Select Time</pre>
11	Press the "0" key and the screen will now display:	<pre>Enter Device (Numbers 1-256) Number> Yes= Finish Time</pre>
12	Enter the slot number that you want to add a device to (e.g. 125) then press the "YES" key and the Screen will now display:	<pre> **Logon Options** > Logon Slot :125 < Slot is :FREE Yes= Select Time</pre>
13	Press the "∇" key until the screen displays:	<pre> Slot is :IN USE >Logon is DISABLED< /\V\V\V\V\V\V\V\ </pre>
14	Press the "YES" key and the screen will now display:	<pre> Slot is :IN USE >Logon is ENABLED < /\V\V\V\V\V\V\V\ </pre>
15	Press and hold the logon button, (as shown in Figure 1 above), for 2-3 seconds, and the screen will now display:	<pre>Logon Default Device 125 Yes= Select Time</pre>
		<pre>Added Default Device 125 Yes= Select Time</pre>

16 Press the "YES" key twice and the screen will now display:




17 Press the "NO" key three times and the screen will now display:



Note: After logging the device on to the system there may be two faults:- 1st fault is processor reset. 2nd fault is the Tamper. (Make sure the device tamper is clear by stabilising the dome sounder, as explained in section 3, then press the silence and reset buttons to clear the faults). The tamper fault will only appear when switch 1 (Tamper Disable Switch) is set to the "Off" position, thus enabling the tamper feature, as explained in Section 3.

18 After the faults have been cleared, turn the control key to the "OFF" position and the screen will display:



2. Sounder volume

The dome's sounder volume can be adjusted using the switches as shown below in Figure 2.

The switch settings for the volume are dispatched as HIGH volume, with switches 3 & 4 both in the "On" position.

	High	HIGH (Default)	Medium	Low
Switch settings	3 On, 4 Off	3 & 4 On	3 Off, 4 On	3 & 4 Off

Figure 2

Sounder switches are exposed when removing the AA battery as shown below in Figure 3.



Figure 3

EMS 5000 FIREPOINT

Sounder switches shown below in Figure 4.



Figure 4

Sounder Volume Switches (Where the Switch in an Upwards orientation = the On Position)

Sounder Configuration Label, shown below in figure 5.




Figure 5

Sounder Dome Configuration Sticker

Note: The Sensitivity switches are not used on this model.

3. Unit Tamper

To enable the tamper facility, switch number 1 will need to be set to the "Off" position. Alternatively, to disable the tamper facility, switch number 1 will need to be set to the "On" position. The dome sounder has a built in tilt bottle, that once tilted, the device will generate a tamper event. Switch number 1 is shown in Figure 5 above. (It can be seen in the figure above that the tamper facility is disabled).

Additional protection can be made by fitting the supplied anti tamper screws.



PLEASE NOTE:
Tamper Knockout
requires removal in order
to fit the Anti Tamper
Screw

4. Dome Sounder Installation

When installing, ensure all dome sounders are sited in accordance with survey and design details.

The mounting plate is shown in Figure 6. The plate can be removed by turning the mounting plate in an anticlockwise rotation, whilst holding the sounder/dome section.



Figure 6

Affix the mounting plate to the ceiling or wall using no.8 countersunk screws with suitable fixings. Ensure that the sounder orientation is correct, and that countersunk head screws are used so as to prevent the possibility of damaging the internal components.

Once the mounting plate is in place, the device can be installed to its location by twisting the sounder/dome section clockwise onto the mounting plate.



Third Party Accredited
ISO 9001 ■ ISO 13485 ■ ISO 14001

The information contained within this literature is correct at time of publishing. The EMS Security Group Ltd reserves the right to change any information regarding products as part of its continual development enhancing new technology and reliability. The EMS Group advises that any product literature issue numbers are checked with its head office prior to any formal specification being written.