

# Wireless Asset Protection Transmitter *Product Datasheet*

## Key Features

- Fully wireless
- Quick and easy installation
- Offers movement & vibration detection
- Small and discreet
- Up to 1 Year battery life



## Product Overview

The wireless asset protection transmitter is ideal for the safeguarding of high value items, particularly paintings and associated artifacts, or where a high integrity alarm detector is required without the need for unsightly or expensive cable installations.








The device is built around a high sensitivity detector coupled to a UHF wireless transmitter. When movement is above a factory set limit, the wireless transmitter sends its alarm signal to a remote radio receiver located within the protected premises.

For picture protection, the unit is provided with gold plated suspension springs which are attached to the horizontal stretcher along the top rear of the painting.

The unit is powered by two 3-volt lithium cells and under normal usage, these cells should last a minimum of one year.

When installed in conjunction with the EMS Iris+ receiver, up to 256 individual transmitters can be individually identified by the receiver.

## Technical Data

- |   |  |  |
|---|--|--|
|  -10 to 55 °C<br>Up to 75% non-condensing |  2x 3V BA3V lithium batteries                         |  7930 (Asset protection transmitter)<br>7206 (Optional wall mounting bracket) |
|  66(h) x 37(w) x 17(d)mm                  |  UHF 458.5 - 459.5MHz<br>25 KHz (MPT 1329)<br>1mW ERP |  |
|  25.35g                                   |  EN50131 class 2 grade 2                              |  |