

DUAL SMOKE & HEAT DETECTOR WITH SOUNDER BEACON

Product datasheet

Key features

- Fully wireless
- Quick and easy to install
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Includes part 23 beacon
- Inbuilt locking mechanism
- Also available without sounder and beacon



Technical data

Operating / storage without batteries: -10 to +55 °C	Smoke: Normal*†, Normal+AVF, Heat: 58 °C static (A2S)*†, 58 °C rate of rise (A2R)*, 72 °C static (BS)* & 72 °C rate of rise (BR)*	CE BOSEC ICA/SA
Storage with batteries: -10 to +30 °C	* EN54 approved sensitivities † Default dual sensitivities	
3 x AA ER14505M lithium thionyl chloride batteries (Fanso or Titus)	93 dB(A) at 1 m max. See the 'Sounder Data' document (MK103) for details	0359-CPR-00268
IP21C - Indoor use only	32 selectable sounder tones	EN54-3, EN54-5, EN54-7, EN54-13, EN54-23 & EN54-25
868 MHz	C-3-12 / 0.5 Hz	SC-23-0210-0001-WZ (Red flash)
14 dBm / 25 mW	110 x 61 mm (Ø x D)	SC-23-0220-0001-WZ (White flash)
X5 (signalling protocol)	0.2 kg	