

WIRELESS CALL POINT (KAC FRONT)

Product datasheet

Key features

- Dual band 868 MHz operation
- Fire indication LED
- Resettable element
- Anti tamper locking
- Protective cover
- Third party EN certified



Product overview

The FireCell wireless call point is quick and easy to install and offers individual addressing at the fire control panel.

Features include dual band 868 MHz operation, auto adjusting power output, fire indication LED, resettable element, anti tamper and a test key.

A transparent hinged cover is also included, for protection against accidental operation in busy environments.

This device has third party EN certification and is compatible with the EMS FireCell system including the Fusion RLM.

Technical data



-10 to 55 °C



6 x AA Alkaline (*Panasonic LR6AD
Powerline / Varta 4006 Industrial*)



IP24, indoor use only



868 MHz



Up to 1250 m (*clear line of site*)*



0 to 14 dBm (*auto adjusting*)



X (*signalling protocol*)



89 x 92 x 70 mm (*W x H x D*)



0.4 kg



CE UK CA **BOSEC**



0359-CPR-0038



EN54-11 & EN54-25



FC-200-002
WIRELESS RED MCP C/W
PROTECTIVE LID

FC-FGCOVER
PROTECTIVE COVER FOR
WIRELESS MCP FC-200-002

**Line of sight refers to the maximum distance over which radio frequency signals can travel in a direct, unobstructed path between transmitter and receiver.*