

DUAL SMOKE & HEAT DETECTOR WITH SOUNDER BEACON

Product datasheet

Key features

- Fully wireless
- Quick and easy to install
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Includes part 23 beacon
- Inbuilt locking mechanism
- Also available without sounder and beacon



Technical data

 Operating / storage without batteries: -10 to +55 °C Storage with batteries: -10 to +30 °C	 Smoke: Normal*†, Normal+AVF, Heat: 58 °C static (A2S)*†, 58 °C rate of rise (A2R)*, 72 °C static (BS)* & 72 °C rate of rise (BR)* * EN54 approved sensitivities † Default dual sensitivities	      
 3 x 3.6 V lithium thionyl chloride batteries. <i>Fanso: ER14505M</i> <i>HCB: ER14505M (HCB-JS-TZ-02-547)</i>	 93 dB(A) at 1 m max. See the 'Sounder Data' document (MK103) for details	 0359-CPR-00268  EN54-3, EN54-5, EN54-7, EN54-13, EN54-23 & EN54-25
 IP21C. Type A: Indoor use only	 32 selectable sounder tones	 SC-23-0210-0001-WZ (Red flash) SC-23-0220-0001-WZ (White flash)
 868 MHz	 C-3-12 (White flash) C-3-9.5 (Red flash)	 emsgroup.co.uk
 14 dBm / 25 mW	 110 x 61 mm (Ø x D)	
 X5 (signalling protocol)	 0.2 kg	