

WALL MOUNTED SOUNDER BEACON











Product datasheet

Key features

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Includes part 23 beacon
- Unique design
- Inbuilt locking mechanism
- Available in red or white and with red or white flash



Technical data

 Operating / storage without batteries: -10 to +55 °C	 X5 (signalling protocol)	   
Storage with batteries: -10 to +30 °C	 110 x 77 mm (Ø x D)	  
 3 x 3.6 V lithium thionyl chloride batteries. <i>Fanso: ER14505M</i> <i>HCB: ER14505M (HCB-JS-TZ-02-547)</i>	 0.20 kg	 0359-CPR-00428
 95 dB(A) at 1 m max.* <i>*See the 'Sounder Data' document (MK103) for details</i>	 32 selectable sounder tones	 EN54-3, EN54-13, EN54-23 & EN54-25
 IP33. Type B: for indoor/outdoor use	 W-2.4-6 (White flash) W-3-5.11 (Red flash)	 SC-32-0110-0001-WZ (Red with red flash) SC-32-0120-0001-WZ (Red with white flash) SC-32-0210-0001-WZ (White with red flash) SC-32-0220-0001-WZ (White with white flash)
 868 MHz	 14 dBm / 25 mW	 emsgroup.co.uk