

DUAL SMOKE & HEAT DETECTOR WITH SOUNDER

Product datasheet

Key features

- Fully wireless
- Quick and easy to install
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Inbuilt locking mechanism
- Also available without sounder



Technical data

 Operating / storage without batteries:
-10 to +55 °C

Storage with batteries:
-10 to +30 °C

 3 x 3.6 V lithium thionyl chloride batteries.
Fanso: ER14505M
HCB: ER14505M (HCB-JS-TZ-02-547)

 IP21C. Type A: Indoor use only

 868 MHz

 14 dBm / 25 mW

 X5 (signalling protocol)

 Smoke: Normal*†, Normal+AVF,
Heat: 58 °C static (A2S)*†, 58 °C rate of rise (A2R)*, 72 °C static (BS)* & 72 °C rate of rise (BR)*

*** EN54 approved sensitivities
† Default dual sensitivities**

 89 dB(A) at 1 m max.
See the 'Sounder Data' document (MK103) for details

 32 selectable sounder tones

 110 x 61 mm (Ø x D)

 0.2 kg

   
  

 0359-CPR-00268

 EN54-3, EN54-5, EN54-7, EN54-13 & EN54-25

 SC-22-0200-0001-WZ

 emsgroup.co.uk