

# CEILING MOUNTED SOUNDER BEACON

## Product datasheet

### Key features

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Includes part 23 beacon
- Unique design
- Inbuilt locking mechanism
- Available in red or white and with red or white flash



### Technical data

Operating / storage without batteries: -10 to +55 °C	X5 (signalling protocol)	CE	BOSEC	ICASA
Storage with batteries: -10 to +30 °C	110 x 79 mm (Ø x D)	FG	DBI	UKCA
3 x 3.6 V lithium thionyl chloride batteries. <i>Fanso: ER14505M</i> <i>HCB: ER14505M (HCB-JS-TZ-02-547)</i>	0.20 kg	DoP	0359-CPR-00428	
IP33. Type B: for indoor/outdoor use	92 dB(A) at 1 m max.* <i>*See the 'Sounder Data' document (MK103) for details</i>	EN	EN54-3, EN54-13, EN54-23 & EN54-25	
868 MHz	32 selectable sounder tones		SC-33-0110-0001-WZ (Red with red flash)	
14 dBm / 25 mW	C-3-12 (White flash) C-3-9.5 (Red flash)		SC-33-0120-0001-WZ (Red with white flash)	
			SC-33-0210-0001-WZ (White with red flash)	
			SC-33-0220-0001-WZ (White with white flash)	

[emsgroup.co.uk](http://emsgroup.co.uk)