

Features:

- ◆ Maintenance-free operation
- ◆ Stable quality and high reliability
- ◆ Compact design
- ◆ 5 years design time (at 25°C)



Applications

- ◆ UPS
 - ◆ Emergency lighting
 - ◆ Fire alarm and security systems
 - ◆ Telecommunication system
 - ◆ Backup power for testing and measuring instruments
 - ◆ Alarm and security system
 - ◆ Electronic apparatus and equipment
 - ◆ Communication power supply
 - ◆ DC power supply
 - ◆ Auto control system

Specifications

Nominal Voltage	6V(3cells)	Operationg Temp Range	Discharge: -15—50°C(5—122°F)	
Nominal Capacity	5.0AH (20hr,1.75V/cell,25°C/77°F)		Charge : 0—40°C(32—104°F)	
	4.2AH (5hr,1.75V/cell,25°C/77°F)		Storage : -15—40°C(5—104°F)	
	3.14AH(1hr,1.60V/cell,25°C/77°F)	Nominal Operating Temp. Range	25±3°C(77±5°F)	
Dimension	Length	70±1mm	Cycle Use	7.2~ 7.4V(25°C/77°F)Temp.Coefficient-15mV/°C
	Width	47± 1mm		Initial Charging Current Less than 1.50A
	Container Height	100±2mm	Standby Use	6.75 V~6.90 V(25°C/77°F)Temp.Coefficient-10mV/°C
	Total Height(with Terminal)	106±2mm		No limit on Initial Charging Current
Weight	840 G ± 3%	Capacity affected by Temperature	40°C(104°F)	103%
Terminal	F1		25°C(77°F)	100%
Container Material	ABS UL 94 V0		0°C(32°F)	86%
Max. Discharge Current	50A(5S)	Self Discharge	CASIL CA series batteries may be stored for up to 6months at 25°C(77°F)and then a freshening charge is required.	
Internal Resistance	Approx 20mΩ		For higher temperatures the time interval will be shorter.	

Constant Current Discharge(Ampere at 25°C/77 °F)

F.V/Time	5min	10min	15min	30min	45min	60min	3h	5h	10h	20h
1.60V/cell	16.0	12.5	8.81	4.71	4.00	3.14	1.30	0.886	0.469	0.260
1.70V/cell	15.4	12.0	8.27	4.53	3.84	3.08	1.28	0.864	0.459	0.255
1.75V/cell	15.1	11.8	8.16	4.45	3.76	3.04	1.25	0.850	0.450	0.250
1.80V/cell	14.8	11.5	7.97	4.37	3.69	3.00	1.23	0.836	0.441	0.245





Constant Power Discharge(Watts per cell at 25°C/77 °F)

F.V/Time	5min	10min	15min	30min	45min	60min	3h	5h	10h	20h
1.60V/cell	28.7	22.5	17.2	8.43	7.57	6.23	2.60	1.77	0.936	0.520
1.70V/cell	27.6	21.6	16.8	8.14	7.29	6.19	2.55	1.74	0.921	0.510
1.75V/cell	27.0	21.1	16.5	7.93	7.14	6.13	2.50	1.70	0.900	0.500
1.80V/cell	26.6	20.8	16.3	7.79	7.00	6.06	2.45	1.66	0.879	0.490

Note: The above characteristics data are average values obtained within three charge/discharge cycles, not the minimum values.


Dimensions
Unit:mm [Inches]

Terminal




NO.:G65001


Storage characteristics




FLOAT SERVICE LIFE




Charge characteristic Curve for standby use




Cycle Life in Relation to Depth of Discharge



Discharge characteristic Curve



Temperature Effects in Relation to Battery Capacity



This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice.